SHEET NO.	LOCATION (SEE SHEETS 15, 16 AND 17 FOR ADDITIONAL INFORMATION ON STREET NAME (N., S., E. OR W.) AND ADDITIONAL STATE OR FEDERAL ROUTES)	SIDE	632 LOOP DETECTOR LEAD-IN CABL, 2 CONDUCTOR, NO. 14 AWG	POWER CABLE, 3 CONDUCTOR, NO. 2 AWG	POWER SERVICE, AS PER PLAN	COMBINATION SIGNAL SUPPORT, TYPE TC-12.30, DESIGN 5, AS PER PLAN	COMBINATION SIGNAL SUPPORT, TYPE TC-12.30, DESIGN 6, AS PER PLAN	COMBINATION SIGNAL SUPPORT, TYPE TC-81.20, DESIGN 4, AS PER PLAN	COMBINATION SIGNAL SUPPORT, TYPE TC-81.20, DESIGN 12, AS PER PLAN	PEDESTAL, 8'	REMOVAL OF TRAFFIC SIGNAL INSTALLATION, AS PER PLAN
			LIN. FT.	LIN. FT.	EACH	EACH	EACH	EACH	EACH	EACH	EACH
15	CONT. TO PB2 TO PB3		68								
15	CONT. TO PB2 TO PB4		89								
15	P1 (6+56.22)	RT.				1					
15	P2 (7+00.43)	LT.							1		
15	PD1 (6+47.78)	LT.								1	
15	PD2 (7+07.68)	RT.								1	
15	WASHINGTON ST.										1
16	CONT. TO PB2		44								
16	CONT. TO PB2 TO PB4 TO PB1		141								
16	CONT. TO PB2 TO PB3		91								
16	P1 (9+56.91)	RT.					1				
16	P2 (10+29.58)	LT.				1					
16	PD1 (10+48.76)	RT.								1	
16	PD2 (9+70.28)	LT.								1	
16	S.R. 83 (CLAY ST.)										1
17	CONT. TO PB1		20								
17	CONT. TO PB1 TO PB4 TO PB5 TO PB2		132								
17	P1 (13+42.65)	RT.						1			
17	P2 (12+99.68)	LT.						1			
17	PD1 (13+50.51)	LT.								1	
17	PD2 (13+02.48)	RT.								1	
17	MONROE ST.										1
15-17 AND 19	VILLAGE HALL TO WASHINGTON ST. TO S.R. 83 (CLAY ST.) TO MONROE ST.			850	1						
	TOTALS		585	850	1	2	1	2	1	6	3
	TOTALS CARRIED TO GENERAL SUMMARY		585	850	1	2	1	2	1	6	3

SHEET NO.	LOCATION (SEE SHEETS 15, 16 AND 17 FOR ADDITIONAL INFORMATION ON STREET NAME (N., S., E. OR W.) AND ADDITIONAL STATE OR FEDERAL ROUTES)	SIDE	633 CONTROLER, TYPE170E WITH 336 CABINET AND ACCESSORIES		CONTROLLER, MISC.: MASTER/SECONDARY COORDINATOR, AS PER PLAN	CONCRETE FOR CABINET FOUNDATION	CONTROLLER ITEM, MISC.: PREEMPT PHASE SELECTOR		CONTROLLER ITEM, MISC.: PREEMPTION DETECTOR		CONTROLLER ITEM, MISC.: PREEMPT CONFIRMATION LIGHT	CONTROLLER ITEM, MISC.: SIGNAL CABLE, PREEMPTION DETECTOR, 4 CONDUCTOR, NO. 20 AWG
			EACH		EACH	C.Y.	EACH		EACH		EACH	LIN. FT.
15	CONT. (7+00.43)		1		1		1					
15	I								1			
15	J								1			
15	PCL1										1	
15	PCL2										1	
15	CONT. TO J											57
15	CONT. TO PB2 TO PB4 TO PB1 TO P1 TO I											214
16	CONT. (10+29.67)		1		1	1.00	1					
16	I								1			
16	J								1			
16	K								1			
16	L								1			
16	PCL1										1	
16	PCL2										1	
16	PCL3										1	
16	PCL4										1	
16	CONT. TO PB2 TO P2 TO J											86
16	CONT. TO PB2 TO P2 TO L											61
16	CONT. TO PB2 TO PB4 TO PB1 TO P1 TO K											197
16	CONT. TO PB2 TO PB4 TO PB1 TO P1 TO I											205
17	CONT. (13+42.65)		1		1		1					
17	I								1			
17	J								1			
17	PCL1										1	
17	PCL2										1	
17	CONT. TO J											45
17	CONT. TO PB1 TO PB4 TO PB5 TO PB2 TO P2 TO I											179
	TOTALS		3		3	1.00	3		8		8	1044
	TOTALS CARRIED TO GENERAL SUMMARY		3		3	1.00	3		8		8	1044

SHEET NO.	LOCATION (SEE SHEETS 15, 16 AND 17 FOR ADDITIONAL INFORMATION ON STREET NAME (N., S., E. OR W.) AND ADDITIONAL STATE OR FEDERAL ROUTES)	SIDE				
	TOTALS					
	TOTALS CARRIED TO GENERAL SUMMARY					

CALCULATED | CHECKED

SIGNALIZATION SUB-SUMMARY

HOL-39-17.36

\millers\386710\cadd\TS03 Thu May 15 10:15:36 1997